



THE HARRIS PRODUCTS GROUP
A LINCOLN ELECTRIC COMPANY
4501 Quality Place • Mason, OH 45040 U.S.A Tel: 513-754-2000 Fax: 513-754-6015
C/Arq Ricard Giralt s/n • Figueres, E-17600 SPAIN
Tel: +34-972-678-826 Fax: +34 972 505 143
TECHNICAL SPECIFICATION SHEET

Harris L-CuP7 BRAZING FILLER METAL

NOMINAL CHEMICAL COMPOSITION:

Cu %	P %	Others %
Balance	6,6 – 7,4	0,25

PHYSICAL AND MECHANICAL PROPERTIES:

Tensile strength (N/mm ²)	Specific Weight (gr/cm ³)	Melting range (°C)	Elongation (%)	Fluidity rating ()	Joint clearance (MM)
250	8,05	710 – 820	5	6	0,05 – 0,10

BRAZING PROPERTIES:

Designed primary for copper to copper brazing applications, L-CUP7 may be used on not high responsibility Brass / Bronze brazing applications. L-CUP7 is an economical alloy for use where joint clearances are close. It flows quickly.

AVAILABLE FORMS:

Standard wire diameters (rods, coils and spools), preformed rings, bend returns on different length and sizes.

SPECIFICATION COMPLIANCE:

ISO 17672	CuP 180
DIN EN1044	CP 202
DIN8513	L-CUP7
AWS A5.8	BCUP-2
NFA 81-362	07B1
BS 1845	CP3

RECOMMENDED FLUX:

Not required on copper to copper applications (Self fluxing). Stay-Silv White or Black brazing flux with copper to Brass or Brass to Brass applications.

APPLICATIONS:

HVAC/R industry: Copper to copper joints where the clearance is between 0,05 – 0,10 MM.

WARNING: PROTECT yourself and others. Read and understand this information.

FUMES AND GASES can be hazardous to your health.

- Before use, read and understand the material Safety Data Sheets (MSDS), and your employer's safety practices.
- Keep your head out of fumes.
- Use enough ventilation, exhaust at the arc, or both, to keep fumes and gases from your breathing zone and the general area.
- Wear correct eye, ear, and body protection.

All statements, information and data given are believed to be accurate and reliable but are presented without guarantee, warranty or responsibility of any kind, expressed or implied. Additional information available at our web site: www.harrisproductsgroup.com ISO 9001.